

JOWFE CO. FOR OIL TECHNOLOGY

FAX: 21861- 9092265,3372563

TEL: 21861-3389505-3389520

INFO @ JOWFE.LY

P.O BOX: 9019 / BENGHAZI – LIBYA



Announcement for general Bid-Bids
Jowfe Company For Oil Technology announces purchasing of the following

MATERIAL	ORDER REF.	QUANTITY	SPECIFICATION
AS ATTH.	CMT-012-11	AS ATTH.	AS ATTH.

We urge manufacturing and Supplying companies those consider them selves qualified to supply the above tubular inspection spare parts to submit their offers according to the following terms and conditions:-

- 1- Offer validity should be defined. (**Max possible validity**).
 - 2- Freight charge must be at Benghazi port (**CFR**).
 - 3- Payment terms should be defined (**Prefer. Cash. Against Documents CAD**).
 - 4- Bid closing date is (**3**) weeks.
 - 5- Suppliers should send two separate offers.
- *- Technical offer (un-priced) to be addresser to the materials in sealed envelope a copy to be faxed or Emailed to the sealed
- *- Commercial offer
- If less than 10, 000.00 Euro (ten thousand) to be addressed to the Materials Manager by fax of E.maill.
 - If the commercial offer is more than 10, 000.00 Euro (ten thousand) it should be sent in sealed envelope and addressed to the chair man of the purchasing committee.

JOWFE CO. FOR OIL TECHNOLOGY

015 km GAMINES ROAD

-P.O. BOX 9019 BENGHAZI – LIBYA.

↳ Required Documents:

- Original commercial invoice.
- Authenticated certificate of origin.
- Original bill of lading (**B/L**). (3 origin)
- Packing list
- Bank details
- Inspection certificate [IF REQUIRED].

Documents should be notarized by the Libyan bureau.

In case the received materials were out of specifications, supplier will be obliged to take all responsibilities.

* Documents should be notarized by the Libyan Bureau.

Best Regards
Eng. Massoud Eddhib
Materials Manage

CEMENT PUMPING TRUCK	QTY: 2 units
Equivalent to the following specifications:	Engine: Type Caterpillar 3406 or GMC or Detroit Approx. power: 500 HP Approx. RPM 2,100 Transmission : Type Allison CIT754 Triplex Pump: Type SP500
These two units should be “brand new”: (i.e. date of manufacture) 2011 down to 2009, <u>but not refurbished</u> models.	
The Trailer Truck with suitable truck for desert conditions 6x6-all wheel drive. Able to deliver 40 tons of cement to well site in one (1) trip. The Truck is fitted with air compressor and able to transfer cement minimum at 250 cu. Ft/min.	
CEMENTING PUMPING UNIT	QTY: 2 units
These two units should be “brand new”: (i.e. date of manufacture) 2011 down to 2009, <u>but not refurbished</u> models.	
CEMENTING PUMPING UNIT with 10,000 psi WP, has a total maximum hydraulic Horse power of 500 hhp, equipped with plungers to operate at a pump rate of at least 5-6 BPM and 8000 psi discharge, diesel powered equipped with over speed shutdown, water cooled and insulated exhaust manifold. The unit is equipped with 2 x 10 bbls. displacement tanks circulating mixer and 45 cu. ft. of cement surge tank complete with: <ul style="list-style-type: none"> a) Cementing manifold from pump to cement and testing lines. b) Pulsation damper c) Centrifugal charge pump to pressurized cement pump section d) Cement mixer capable of mixing high density cement e) Control Console with pressure gauges, pump rate meter and Barrel Counter for each pump. f) Built-in with Air compressor g) One-double Pen Pressure Recorder with 0- 10,000 psi working pressure h) Re-circulating mixing unit with automatic Density Control i) Computer for monitoring/data requisition system 	
The cement pump will be used for:	
<ul style="list-style-type: none"> A) Primary & Remedial cementing work B) Pressure Testing up to 7000 psi C) Plug and Abandonment D) General Pumping operation 	
STEEL PUMPING LINES	QTY : 2 sets –or 1 set for each Cement Pumping Unit
STEEL PUMPING LINES 2”x 10,000 psi WP Chiksan compete with WECO Hammer Union 1502 with sufficient straight sections, pup joints, adapters, flexible chiksan loops and double wing swing joints.	